

Effects of Binder, Curing Time, Temperature and Trafficking on Moduli of Stabilized and Unstabilized Full Depth Reclamation Materials

Rongzong Wu, Stefan Louw, David Jones
University of California Pavement Research Center

94th Annual Transportation Research Board Meeting
January 11-15, 2015 Washington D.C.

Outline

- **Background**
- **Research Objective**
- **General Approach**
- **Data Collection**
- **Results and Discussion**
- **Summary and Conclusions**

Background

- **FDR = Full Depth Reclamation/Recycling**
- **Caltrans' use of FDR**
 - Started since 2001
 - Mostly using combination of foam asphalt (FDR-FA) and cement (FDR-PC) as stabilizing agent
 - Sometime no stabilization (FDR-NS)
 - Growing interest for using engineering emulsion (FDR-EE)

Research Objective

- **Revised guidelines and specification language for FDR in California**
- **Mechanistic-Empirical (M-E) design and performance parameters for FDR layers**
 - In-situ Stiffness
 - Fatigue damage
 - Rutting (permanent deformation under traffic)

What did others find about FDR stiffness?

■ Quick and Guthrie (2011)

- FDR with emulsion
- Consistently low in the first 2 weeks
- Increase dramatically by 4 months
- Decrease considerably by 1 year

■ Mohammad et al. (2003)

- FDR-FA layer
- More than doubled in the first month

■ Syed and Scullion (2001)

- FDR-PC (i.e., cement)
- Higher cement% leads higher stiffness


General Approach (1/3)

- **Work around the accelerated pavement testing (APT) study**
 - Test cells constructed for the APT
 - Trafficking using heavy vehicle simulator (HVS)
- **FWD at different occasions**
 - Right after construction
 - Right before HVS trafficking
 - Right after HVS trafficking

General Approach (2/3)

■ FWD Testing Protocol

- Twice for each occasion: early morning and mid afternoon
- For testing around HVS:
 - 4-m (before) + 8-m (within) + 4-m (after)
 - 0.5 m interval



General Approach (3/3)

■ Back-calculation

- Kalman-Filter based search algorithm
- Multilayer linear elastic system





Data Collection – The Test Cells



4 lanes at 3.7m wide each,
each cell is 37 m long

Pavement Structure




Data Collection - FWD Testing Schedule

FDR Material	Occasion	Days After Construction
FDR-NS (under 60mm HMA)	After construction	19
	Before Trafficking	57
	After Trafficking	161
FDR-FA	After construction	19
	Before Trafficking	126
	After Trafficking	240
FDR-PC	After construction	19
	Before Trafficking	239
	After Trafficking	540
FDR-NS (under 120mm HMA)	After construction	19
	Before Trafficking	195
	After Trafficking	314




Results and Discussion

Initial Stiffness @19 days




Initial Stiffness @ 19 days

- FDR-NS QQ-Plot for Normal Distribution of Natural Log




Initial Stiffness @ 19 days

■ FDR-FA QQ-Plot for Normal Distribution



Initial Stiffness @ 19 days


■ FDR-PC QQ-Plot for Normal Distribution




Initial Stiffness @ 19 days

Material Type	Approximate Distribution	Average Pavement Temperature	Mean (MPa)	Standard Deviation (MPa)	Coefficient of Variance
FDR-NS	Log-normal	15°C	220	117	0.53
FDR-FA	Normal	20°C	2,959	1,595	0.54
FDR-PC	Normal	19°C	8,925	2,978	0.33

Effect of Pavement Temperature



Effect of Curing Time




Effect of Trafficking + Curing

Matreial	When	Average (MPa)	C.O.V.	ESALs Applied (Mn)	Residual Stiffnes Ratio
FDR-NS with 60 mm HMA	Before	156	0.16	0	1.00
	After	137	0.19	5.1	0.88
FDR-NS with 120 mm HMA	Before	186	0.17	0	1.00
	After	103	0.50	20.8	0.55
FDR-FA	Before	5,100	0.23	0	1.00
	After	1,490	0.19	17.0	0.29
FDR-PC	Before	14,316	0.16	0	1.00
	After	6,064	0.70	43.3	0.42

Effect of Trafficking Alone

Matreial	When	Ratio of (Trafficked) / (Non Trafficked)	Relative Ratio
FDR-NS with 60 mm HMA	Before HVS	1.09	1.08
	After HVS	1.18	
FDR-NS with 120 mm HMA	Before HVS	1.09	0.43
	After HVS	0.47	
	Long After HVS	0.73	
FDR-FA	Before	0.90	0.36
	After	0.32	
FDR-PC	Before	0.90	0.39
	After	0.35	

Effect of Traffic Verification



Conclusions

■ Initial stiffness @ 19 days

- FDR-NS: 200 MPa with c.o.v of 55%
- FDR-FA: 3000 MPa with c.o.v of 55%
- FDR-PC: 9000 MPa with c.o.v of 35%

■ All FDR materials show slight sensitivity to temperature for their stiffness

■ Effects of curing

- 50% increase for FDR-FA
- 80% increase for FDR-PC
- Roughly unchanged for FDR-NS

Conclusions (continued)

■ Effect of Trafficking

- About 60% drop in stiffness
- Likely caused by damage in the FDR layer
- FDR-NS shows re-stiffening after trafficking stopped, not sure whether is permanent

■ Implication for design

- Need to account for damage in the FDR layer
- Curing is also critical.



QUESTIONS?