

Life Cycle Assessment (LCA) of a Thin Bonded Concrete Overlay (BCOA) of Asphalt Project in Woodland, California

Maryam Ostovar

Ali Butt

Angel Mateos


John Harvey

13 January 2021




Introduction

- **Thin bonded concrete overlay** of asphalt (BCOA), or **thin whitetopping**:
 - a rehabilitation alternative consisting of a 100 to 175 mm concrete overlay on an existing **flexible** or **composite** pavement
- Thin BCOA has been used as a 20-year **design life** rehabilitation alternative for asphalt pavements in fair to good condition under low and intermediate traffic levels.
- During the life of the BCOA pavement, the materials and construction stages of thin BCOA result in significant environmental impacts, in terms of
 - **energy** use,
 - **material** resource consumption,
 - **emissions**
- This paper demonstrates the use of LCA to quantify and evaluate the environmental impacts of alternative materials, construction and designs for a BCOA pilot project that has been implemented in **Woodland, California**.




Introduction- Life Cycle Assessment



UCPRC LCA framework- Major life-cycle stages of a pavement (Harvey et al. 2016)

Goal and scope

- The **goal** of this study was to **quantify** the potential environmental impacts due to material and construction stages of thin BCOA.
- The LCA analysis is focused on a thin BCOA pilot project built in Woodland, California, in 2018-2019.
- The considered layer includes
 - 150 mm PCC overlay on top of a **new rubberized hot mix asphalt (RHMA)**, and
 - 150 mm PCC overlay on top of a **milled old asphalt**.
- The **mix designs** used in the pavement layers of the project, includes
 - PCC Type III used for the HVS test sections with 4 hours opening time (OT) ,
 - PCC Type II/V used for the Woodland project with 24 hours OT, and
 - Normal strength PCC Type II/V used by Caltrans with the 10 days OT,
 - RHMA mix design



A cross-section of the Woodland pilot thin BCOA in SR 113

Scope

- The **scope** of this study was limited to “**cradle-to-laid**” for Woodland pilot project in which the **materials** and **construction** stages as well as **transportation** of materials in the life cycle of the pavements were considered.
 - The use stage and end-of-life were not included in this study’s scope.
- The **functional unit** defined for this study is construction of **1 lane-km** of pavement surface.
- The **material stage** includes
 - extraction of raw materials from the ground,
 - transportation to processing plants, and the plant processing,
 - transportation of the materials from the plant to the site.
- The intended **audience** of the study includes
 - local governments,
 - pavement researchers and practitioners,
 - pavement designers



Life Cycle Inventories (LCI)

Different considered BCOA cases

	Case Number	Material	Concrete Thickness mm (inch)	RHMA Thickness mm (inch)
6 in PCC Layer	1-A (PCC on top of old HMA)	HVS PCC Type III (4-hr OT)+ Tie Bar	150 (6)	---
	1-B	HVS PCC Type III (4-hr OT)+ Tie Bar+ RHMA	150 (6)	30 (1.2)
	2-A (PCC on top of old HMA)	Woodland PCC Type II/V (24-hr OT)+ Tie Bar	150 (6)	---
	2-B	Woodland PCC Type II/V (24-hr OT)+ Tie Bar+ RHMA	150 (6)	30 (1.2)
	3-A (PCC on top of old HMA)	Caltrans normal strength PCC Type II/V (10-day OT)+ Tie Bar	150 (6)	---
	3-B	Caltrans normal strength PCC Type II/V (10-day OT)+Tie Bar+ RHMA	150 (6)	30 (1.2)
5 in PCC Layer	4-A (PCC on top of old HMA)	HVS PCC Type III (4-hr OT)+ Tie Bar	125 (5)	---
	4-B	HVS PCC Type III (4-hr OT)+ Tie Bar+ RHMA	125 (5)	30 (1.2)
	5-A (PCC on top of old HMA)	Woodland PCC Type II/V (24-hr OT)+ Tie Bar	125 (5)	---
	5-B	Woodland PCC Type II/V (24-hr OT)+ Tie Bar+ RHMA	125 (5)	30 (1.2)
	6-A (PCC on top of old HMA)	Caltrans normal strength PCC Type II/V (10-day OT) + Tie Bar	125 (5)	---
	6-B	Caltrans normal strength PCC Type II/V (10-day OT)+Tie Bar+ RHMA	125 (5)	30 (1.2)

- The LCI database created by the UCPRC was used in this study including the details of model development, data sources, and the assumptions.

Energy Input for 1 kg of PCC

Electricity	0.00618 MJ
Natural Gas	0.000122 m ³
Diesel	2.54E-007 m ³

Energy Input for 1 kg of RHMA

Electricity	0.0076319 MJ
Natural Gas	0.0103261 m ³

Life Cycle Impact Assessment (LCIA)

The life cycle impact assessment categories selected to be reported in this study includes

- Global Warming Potential (**GWP**): in kg of CO₂e.
- Photochemical Ozone Creation Potential (**POCP**): in kg of O₃e (a measure of smog formation).
- Human Health Particulate Matters (**PM_{2.5}**): in kg of PM_{2.5} (particulate matters smaller than or equal to 2.5 micrometers in diameter).
- Renewable Primary Energy Demand (**PED-R**) used as fuel from renewable resources (net calorific value excluding feedstock energy): in MJ.
- Non-renewable Primary Energy Demand (**PED-NR**) used as fuel from nonrenewable re-sources (net calorific value excluding feedstock energy): in MJ.
- Feedstock Energy (**PED-FS**) is Primary Energy Demand used as a material from nonrenewable resources (also called PED (non-fuel)): in MJ.
 - **Feedstock energy** is a primary energy demand stored in the construction materials (such as asphalt) that is not consumed.



LCI data

PCC and RHMA Mix Designs, and Number of Tie bars in BCOA layers

<i>HVS PCC Mix Design Type III (4-hour OT)</i>			<i>Woodland PCC Type II/V Mix Design (24-hour OT)</i>			<i>Normal Strength PCC Type II/V Mix design (10-day OT)</i>			<i>RHMA Mix Design</i>	
<i>Material</i>	<i>Mass per Volume (lb/yd³)</i>	<i>% by mass</i>	<i>Material</i>	<i>Mass per Volume (lb/yd³)</i>	<i>% by mass</i>	<i>Material</i>	<i>Mass per Volume (lb/yd³)</i>	<i>Percentage by mass</i>	<i>Material</i>	<i>% by mass</i>
Accelerator	37.436	0.89	Accelerator	0.00	0.00	Accelerator	76	1.62	Crushed	92.50
Flyash	0.00	0.00	Flyash	101	2.55	Flyash	704.153	15.00	Natural	0
Crushed Aggregate	1787	31.86	Crushed Aggregate	1200	30.34	Crushed Aggregate	1350	28.76	Bitumen	6.00
Natural Aggregate	1348	42.23	Natural Aggregate	1787	45.18	Natural Aggregate	1875	39.94	Extender oil	0.15
Type III Portland Cement	799	18.88	Type II/V Portland Cement	574	14.51	Type II/V Portland Cement	429	9.14	Crumb Rubber Modifier (CRM)	1.35
Retarder	4	0.095	Retarder	0.897	0.023	Retarder	0.2	0.004	Polymer	0
Water Reducing Admixture	6.25	0.15	Water Reducing Admixture	1.614	0.041	Water Reducing Admixture	2	0.040	RAP	0
Water	250	5.91	Water	291	7.36	Water	258	5.50		
Number of Tie bars										
Number of tie bars per slab (slabs are 6 ft long)						2				
Number of tie bars per 1 km						1094				

LCI and LCIA

Construction Information

Layer	Equipment/ Activity	Engine Power	Hourly Fuel Use	Speed	Time 1Pass 1lane-km for over	No. Passes of	Fuel Used	Total Used Fuel for 1lane-km
		kw(hp)	m3/hr(gal/hr)	km/h(ft/min)	(hr)		m3(gal)	m3 (gal)
PCC	Milling for 25 mm (1 in)	522 (700)	0.076 (20)	0.183 (10)	5.47	1	0.41 (109.36)	0.49 (129.05)
	Sweeping (multiple times)	59.66 (80)	0.008 (2)	1.83 (100)	0.55	2	0.01 (2.19)	
	Wetting	59.66 (80)	0.008 (2)	1.83 (100)	0.55	1	0.004 (1.09)	
	Concrete Placement	67.11 (90)	0.011 (3)	0.183 (10)	5.47	1	0.06 (16.40)	
RHMA	Prime coat application	260.995(350)	0.027 (7.2)	0.457 (25)	2.19	1	0.06 (16.40)	0.54 (143.15)
	RHMA placement	186.43(250)	0.040 (10.6)	0.274 (15)	3.65	1	0.15 (39.62)	
	Rolling (vibratory)	111.86(150)	0.031 (8.1)	0.457 (25)	2.19	2	0.13 (34.34)	
	Rolling (static)	111.86(150)	0.031 (8.1)	0.457 (25)	2.19	3	0.2 (52.83)	

LCI and LCIA


Transportation Information

Material	Transportation	Material in 1lane-km (kg)	No. of trips
PCC Type II	1-way 40 km (25 mile) from plan to the construction field	1,332,000	56
Cement	1-way 692km (430 mile) from cement plant to the mixing plant	193,292	9
RHMA	1-way 56km (35 mile) from plan to the construction field	266,400	12
Bitumen	1-way 435km (270 mile) from refinery to the plant	15,974	1
Crushed Agg.	1-way 40 km (25 mile) from quarry to the plant	246,420	11


Impacts of Material Functional Unit (1 kg) During Production

Material	Unit	GWP (kg CO ₂ e)	POCP (kg O ₃ e)	PM2.5 (kg)	PED-R (MJ)	PED-NR (MJ)	PED-FS (MJ)
HVS PCC Type III (4-hr OT)	1kg	1.78E-01	1.50E-02	9.72E-05	2.08E-01	1.08E+00	0.000E+00
Woodland PCC Type II/V (24-hr OT)	1kg	1.296E-01	1.120E-02	8.502E-05	1.418E-01	8.652E-01	0.000E+00
Caltrans Normal Strength PCC Type II/V (10-d OT)	1kg	1.169E-01	8.228E-03	1.183E-04	1.076E-01	8.150E-01	0.000E+00
RHMA	1kg	5.628E-02	5.977E-03	4.036E-05	9.329E-02	3.408E+00	6.487E+00
Tie Bar	Each	3.343E+00	1.667E-01	1.616E-03	1.443E+00	4.147E+01	0.000E+00


LCIA Results-Emissions



Global Warming Potential results per life cycle stage per pavement layer (Woodland case study)




Smog Formation Potential results per life cycle stage per pavement layer (Woodland case study)




Human Health Particulate Effect results per life cycle stage per pavement layer (Woodland case study)

LCIA Results- Emissions




Global Warming Potential results per life cycle stage per pavement layer (Woodland case study)

LCIA Results-Emissions




Smog Formation Potential results per life cycle stage per pavement layer (Woodland case study)







Human Health Particulate Effect results per life cycle stage per pavement layer (Woodland case study)

LCIA Results- Energy Consumption




Consumed Energy per life cycle stage per pavement layer (Woodland case study)

Sensitivity Analysis- LCIA results in material stage for different alternatives




Sensitivity analysis




Global Warming Potential results in material stage for different alternatives

Sensitivity analysis




Smog Formation Potential results in material stage for different alternatives

Sensitivity analysis



Energy consumptions result in material stage for different alternatives

Sensitivity analysis




Human Health Particulate Effect results in material stage for different alternatives

Interpretation

The important factors leading to major changes in the environmental emissions and energy consumptions in the material stage:

- ✓ **Thickness** of the surface layer.
- ✓ The **new RHMA layer** under the surface rigid layer compared to old HMA under the PCC layer.
 - The results show the **increase** of **8%-13%** in GWP, POCP, PM2.5, and PED-R.
 - The **sharp increase** in **PED-NR (75%)** can also be seen.



Interpretation

The difference in the **concrete mix designs**:

- ✓ HVS PCC Type III mix with 4 hours OT has the highest environmental impacts and energy consumption followed by PCC Type II/V mix designs.
 - **Finer grinding** of Type III PC as well as the higher **amount of cement** in Type III PC compared to Type II/V PC result in the higher environmental impacts.
- ✓ Caltrans normal strength mix has a slightly **lower impacts** in terms of GWP, POCP, and energy consumption compared to the Woodland mix. However, the Caltrans normal strength mix has the **highest impacts** in terms of PM2.5.
 - This might be because of the **higher amount of flyash** in this mix compared to the other mixes.

This paper demonstrates the use of LCA to quantify and evaluate the environmental impacts of alternative materials, construction and designs for a pavement structure.



ACKNOWLEDGMENT

The authors would like to thank Nick Burmas and Joe Holland from the Caltrans Division of Research, Innovation, and System Information for support of this project.

References

- Butt, A.A., Harvey, J.T., Saboori, A., Ostovar, M., and Reger, D. (2019). Airfield Life Cycle Assessment: Benchmark Study of a Project at JFK International Airport. *Airfield and Highway Pavements 2019: Innovation and Sustainability in Highway and Airfield Pavement Technology*, ASCE, P 456-464.
- Butt, A.A., Harvey, J.T., Reger, D., Saboori, A., Ostovar, M., and Bejarano, M. (2019). Life-Cycle Assessment of Airfield Pavements and Other Airside Features: Framework, Guidelines and Case Studies. Research Report, Federal Aviation Administration, Performing Organization No.: DOT/FAA/TC-19/2.
- Butt, A.A. and Birgisson, B. (2016). Assessment of the attributes based life cycle assessment framework for road projects. *Structure and Infrastructure Engineering Journal*. Vol. 12, No. 9. P 1177-1184.
- Butt, A.A., Toller, S., and Birgisson, B. (2015). Life Cycle Assessment for the Green Procurement of Roads: A Way Forward. *Journal of Cleaner Production*, 90: 163-170. DOI: 10.1016/j.jclepro.2014.11.068.
- Harvey, J. T., Meijer, J., Ozer, H., Al-Qadi, I. L., Saboori, and A., Kendall, A. (2016). Pavement Life Cycle Assessment Framework. U.S. Department of Transportation Federal Highway Administration, FHWA-HIF-16-014, July 2016, Washington, DC.
- Harrington, D. S., and G. Fick. (2014). Guide to concrete overlays: Sustainable solutions for re-surfacing and rehabilitation existing pavements. National Concrete Pavement Technology Center.
- ISO (2006). Environmental Management – Life Cycle Assessment – Principles and Framework. International Organization for Standardization, ISO 14040, Geneva, Switzerland.
- Kendall, A. (2012). Life Cycle Assessment for Pavement: Introduction. Presentation in Minutes, FHWA Sustainable Pavement Technical Working Group Meeting, April 25-26, 2012, Davis, CA.
- Mateos, A., J. Harvey, F. Paniagua, J. Paniagua, and R. Wu. (2019). Development of Improved Guidelines and Designs for Thin BCOA: Summary, Conclusions, and Recommendations. University of California Pavement Research Center, Summary Report: UCPRC-SR-2018-01.
- Pacheco-Torgal, F. and Ding, Y. eds. (2013). Handbook of recycled concrete and demolition waste. Elsevier.
- Saboori, A., John Harvey, Ting Wang, and Hui Li. (2018). Documentation of UCPRC Life Cycle Inventory used in CARB/Caltrans LBNL Heat Island Project and other LCA Studies. University of California Pavement Research Center, Davis, CA.



Thanks for Your Attention

Questions?